


MATERIALS SCIENCE

Precision Made Simple

DSX2000 Digital Microscope



EVIDENT

Precision Meets Simplicity

The DSX2000 digital microscope series simplifies tasks, boosts productivity, and streamlines work for researchers and QC lab professionals with smart tools, all-in-one imaging, and a customizable interface.

The DSX2000 microscope series with PRECiV™ software empowers your team to achieve fast, precise results and capture exceptional images. An intuitive, seamless experience enables users of all skill levels to operate the system with ease and confidence.

- **Simplify Operations with an All-in-One Solution**
Get fast, reliable results with a fully integrated system for imaging, measurement, analysis, and reporting.
- **Improve Productivity with Smart Tools**
Speed up inspections with custom workflows and AI-assisted analysis.
- **Assurance in Your Images and Measurements**
See fine sample details in high resolution beyond 4K.



DSX2000 Digital Microscope Series

Choose Your Model

The DSX2000 digital microscope series includes motorized, universal, or standard zoom head options so you can customize the system to your exact imaging and workflow needs. Whether your team needs full automation, advanced functionality, or just the basics, the DSX2000 series has you covered.



Fully Motorized DSX2000 MZH

Full motorization simplifies tasks and boosts productivity so your team can navigate challenges with ease. The motorized zoom head with an automatic revolving nosepiece supports up to four objective lenses for effortless magnification changes and seamless macro to micro inspections. This model is ideal for high-resolution observations and inspection applications requiring efficient go/no-go decisions.



Versatile All-in-One DSX2000 UZH/SZH

Our universal and standard zoom head models enable seamless macro to micro inspections with a single system. The sliding nosepiece supports up to two objective lenses for seamless magnification changes. These models offer the flexibility to use a wide variety of objective lens types, including super long working distance options, and to image your sample from a wide range of angles.

Simplify Operations with an All-in-One Solution

See the Whole Picture

The DSX2000 microscope series offers a wide magnification range of 21X-7,300X, enabling you to complete macro and micro inspections with one system. With a lineup of 20 objective lenses, including super long working distance and high-resolution options, you can easily adapt your imaging to different samples and applications.



Fast and Flexible Macro Imaging


Quickly capture overview images of samples with the macro camera. This flexible accessory can be detached and held by hand to image large samples that cannot be placed on the stage. Switching to the macro camera view in the software is simple, making it easy to alternate between micro and macro imaging. Generate comprehensive reports faster with the required overview and magnified images.




Macro image of sample

Switch Objectives Quickly and Easily


Quickly and easily change objectives on any DSX2000 model. The easy-to-replace lenses and adjustable settings in an ergonomic system let you work faster and maintain comfort.




Objective lens 3X



Objective lens 10X



Objective lens 20X



Objective lens 40X

Switch Automatically

For systems with a motorized zoom head, you can control the automatic revolving nosepiece from either the console or your computer to make effortless magnification changes.

Switch with a Slider


Systems with standard or universal zoom heads also offer seamless magnification changes via the sliding nosepiece, where up to two objective lenses can be attached at the same time. Switch the magnification just by sliding the lens for fast macro to micro imaging. This system makes it easy to change lens types, providing flexibility for various inspection needs.




Simplify Operations with an All-in-One Solution

See What Matters with One Click


The DSX2000 microscope offers seven different observation methods at the click of a button. Find viewing conditions using brightfield (BF), oblique (OBQ), darkfield (DF), MIX (DF and BF), polarization (PO), differential interference contrast* (DIC), or our unique shaded relief (SR) method.




BF Brightfield




MIX Brightfield + Darkfield




PO Polarization




OBQ Oblique



DF Darkfield




SR Shaded relief



DIC Differential interference contrast

BF Brightfield **SR** Shaded relief



Shaded Relief Observation Mode

Reveal ultra-fine, hard-to-see defects in real time, without post-processing delays. Move the stage and scan your sample seamlessly, viewing shaded relief images instantly for fast, thorough inspections.

* Not available on the SZH model.

Simplify Operations with an All-in-One Solution



Find the Best Image, Fast

The best image function reviews all available observation methods for your sample and identifies the best imaging mode for revealing what needs to be seen—all with a simple click.

Adaptable Sample Positioning


The extended stage (up to 200 × 100 mm) accommodates multiple or large samples, while the tilting frame and rotating stage enable you to place your sample in the best observation conditions.




Tilting frame

Lighting Tailored to Your Sample

Observe internal details in transparent, semi-transparent, or thin samples with a variety of transmitted lighting and contrast options. Simply select cartridges according to the type and purpose of the sample.



Plastic molded product Polarization



Fibers Darkfield



Rotational stage




Extended Stage


Improve Productivity with Smart Tools

Customized Workflows for Faster Operation


EZ



Define your workflow



Arrange the icons



Activate the workflow

The Power to Work Smarter

Customized workflows and AI capabilities on the DSX2000 digital microscope give you the power to work smarter, unlocking more efficient ways to perform routine inspections or conduct complex analyses.

Automate Repetitive Tasks

Automate live measurements, edge detection, and other repetitive processes, minimizing operator input and variability while speeding up inspections.

Collect Data Quickly

Powerful interactive measurement tools include edge-detected circles, magic wand, auxiliary lines, object linking, and more.


Unlock Efficiency with AI

PRECiV™ image analysis software equips all Evident industrial microscopes—including the DSX2000 system—with our unique Live AI.


This powerful tool instantly reveals hidden details and highlights key features on live images without the need for additional processing.

AI-assisted decision-making frees your experts from the need to double-check images.


AI



Live image



Train the neural network (5 minutes)




Apply the neural network to the live image

EZ mode simplifies the interface by displaying only essential functions. Supervisors can create custom workflows for operators, limiting available buttons for consistency and ease of use. Operators can get to work quickly with minimal training while reducing the potential for errors.


Improve Productivity with Smart Tools

Eliminates unimportant scratches or elements that could obscure critical information or be mistakenly counted by the AI.

Automatic Image Improvement




Steel microstructure




Live contrast enhancement with grain boundaries highlighted

Image segmentation enables the AI, with minimal training, to identify and count different object types in your sample.

Automatic Object Discrimination



Through holes in printed circuit board



Live detection of filled through holes and empty through holes



Improve Productivity with Smart Tools

Simplify Tasks with Unified Software



PRECiV™ software operates the same way on all our industrial microscopes, creating a cohesive analysis environment. Access tools for 2D/3D measurements, image enhancement, macro recording, AI-assisted analysis, and more.

Maximize Throughput

Analyze images on any PC equipped with PRECiV software. This frees up the DSX2000 microscope for image acquisition, increasing workflow efficiency.


Easier Imaging, Measurement, and Analysis

Access tools for 2D/3D measurements, image enhancement, macro recording, AI-assisted analysis, and more.



Create Compliant Reports Easily

When it's time to present your results, the DSX2000 microscope makes reporting easy. Use the plug-in for Microsoft 365 to design your own reports in Microsoft Word, Excel, or PowerPoint.




Compliant Measurements in a Few Clicks



Simplify daily tasks for material analyses with standard-compliant automated workflows. Choose from options for grain sizing, cast iron analysis, phase analysis, non-metallic inclusion rating, and more.

Seamless Network Integration

Easily connect the DSX2000 microscope to your company network for IT compliance and quick image sharing.



Assurance in Your Images and Measurements



Continuous Autofocus

The objective lens automatically moves up and down to match the unevenness of the object, providing a live image that is always in focus even when the observation location changes. By eliminating the need to adjust focus manually, the DSX2000 microscope helps your lab improve analysis and inspection efficiency.

High-Resolution Imaging Beyond 4K

* Resolution beyond 4K is not available on the SZH model.


The DSX2000 microscope empowers inspections with image quality that surpasses standard 4K resolution*, delivering enhanced clarity and coverage across sample types—whether large, thin, thick, rough, reflective, or transparent. Pair the system with, for example, a 32-inch 4K monitor, to further enhance sample details for observation and analysis.

Confidence in Every Detail

Be confident in your results knowing that the DSX2000 digital microscope produces exceptional images and precise measurements that meet the exacting demands of quality control, failure analysis, and R&D.


HD

Full High Definition Mode




4K

4K Mode




8K

Ultra Mode



Assurance in Your Images and Measurements

Unlimited Image Size



Seamless stitching quickly creates large macro images, enabling analysis of large samples in less time. Create macro images as large as you want—the only limits are your hard drive space and stage travel range.




Save and Recall Observation Conditions

Captured images automatically record their settings, so you can easily recall and reuse conditions with a single click for consistency and repeatability.

Advanced 3D Measurements

Get detailed insights into surface heights and features with precise 3D analysis for complex inspections.



Guaranteed* Accuracy and Repeatability

Telecentric optics and traceable calibration ensure precise measurements and alignment with metrology standards. On-site calibration and service plans keep your DSX2000 microscope compliant at predictable costs, mainly with bundled multi-year plans.




*The guaranteed accuracy and repeatability apply only if the device has been calibrated according to the manufacturer's specifications and is in defect-free condition. Calibration must be performed by an Evident technician or an Evident-authorized specialist.

Integrated Observation Methods

Easily switch between brightfield (BF), oblique (OBQ), darkfield (DF), MIX (BF and DF), simple polarization (PO), differential interference contrast (DIC), and shaded relief (SR). This flexibility enables you to handle almost any microscope inspection task.


BF Brightfield Good for flat samples

On a mirrored surface, scratches look dark against the surface, helping them stand out.




OBQ Oblique Enhance your surface's unevenness

Use this method to enhance a surface's unevenness by shining the light from only one direction. This method is ideal for uneven or corrugated samples and cutting traces.




PO Polarization Designed for polarizing samples

By orthogonally laying out two polarization filters, this method enables you to see the contrast and color according to your sample's polarization property.




DIC Differential Interference Contrast Visualize defects at the nano level

This method enables you to visualize surface unevenness at the nano level. It is ideal for inspecting wafers, film, LCD anisotropic conductive film, and glass surfaces.




DF Darkfield For scratches and similar defects

Scattering or reflected light is obliquely irradiated on the sample's surface, highlighting dust, scratches, and other objects. Dust and scratches appear bright in the visual field.




MIX BF+DF Light comes from around the lens

Easily detect scratches and defects that can be hard to find with a conventional microscope by combining the detection capabilities of darkfield (DF) to the visibility of brightfield (BF).



SR Shaded Relief Reveal defects in real time

Illuminates the sample from different directions, revealing defects as the image is created in real time. Fine surface details are highlighted through shading, enabling clear observation for fast, thorough inspections.



Integrated Observation Methods

Objective Lenses

		20X	40X	100X	200X	500X	1,000X	3,000X	6,000X	10,000X			
	Objective lens model										Working Distance (mm)	NA	Field of View ¹ (μm)
Super long working distance objective lenses Provides a long working distance between the lens and sample 	DSX10-SXLOB1X²	20.9–146.1X									51.7	0.03	18182 × 13317 μm 2597 × 1902 μm
	DSX10-SXLOB3X²		43.8–438.4X								66.1	0.09	8658 × 6341 μm 866 × 634 μm
	DSX10-SXLOB10X²			146.1–1,461X							41.1	0.20	2597 × 1902 μm 260 × 190 μm
High-resolution, long working distance objective lenses Delivers both high resolution and a long working distance 	DSX10-XLOB3X²		43.8–438.4X								30.0	0.09	8658 × 6341 μm 866 × 634 μm
	DSX10-XLOB10X			146.1–1,461X							30.0	0.30	2597 × 1902 μm 260 × 190 μm
	DSX10-XLOB20X			292.3–2,923X							20.0	0.40	1299 × 951 μm 130 × 95 μm
	DSX10-XLOB40X			584.5–5,845X							4.5	0.80	649 × 476 μm 65 × 48 μm
High-performance, high NA objective lenses Delivers high performance at the nanoscale 	MPLFLN1.25X⁴	26.1–182.7X									3.5	0.04	14546 × 10654 μm 2078 × 1522 μm
	MPLFLN2.5X⁴		39.1–365.3X								10.7	0.08	9697 × 7102 μm 1039 × 761 μm
	MPLFLN2.5XBD⁵		39.1–365.3X								8.7	0.08	9697 × 7102 μm 1039 × 761 μm
	MPLFLN5XBD		73.1–730.7X								12.0	0.15	5195 × 3805 μm 519 × 380 μm
	MPLFLN10XBD			146.1–1,461X							6.5	0.30	2597 × 1902 μm 260 × 190 μm
	MPLFLN20XBD			292.3–2,923X							3.0	0.45	1299 × 951 μm 130 × 95 μm
	MPLFLN50XBD			730.7–7,307X							1.0	0.80	519 × 380 μm 52 × 38 μm
	MPLAPON50X³			730.7–7,307X							0.35	0.95	519 × 380 μm 52 × 38 μm
	LMPLFLN10XBD			146.1–1,461X							10.0	0.25	2597 × 1902 μm 260 × 190 μm
LMPLFLN20XBD			292.3–2,923X							12.0	0.40	1299 × 951 μm 130 × 95 μm	
LMPLFLN50XBD			730.7–7,307X							10.6	0.50	519 × 380 μm 52 × 38 μm	
MXPLFLN20XBD			292.3–2,923X							3.0	0.55	1299 × 951 μm 130 × 95 μm	
MXPLFLN50XBD			730.7–7,307X							3.0	0.80	519 × 380 μm 52 × 38 μm	

¹ Magnification and field of view are based on a 27-inch 4K monitor, scale setting: 175%, anti-vibration mode: off, fit to window mode, image aspect ratio: 4:3.


² The DSX10-SXLOB1X, 3X, 10X, and DSX10-XLOB3X do not support PO observation.

³ The MPLAPON50X does not support DF, MIX, or SR observations.

⁴ The MPLFLN1.25X and 2.5X do not support DF, MIX, PO, DIC, or SR.

⁵ The MPLFLN2.5XBD does not support PO or DIC observations.

DSX2000 System Chart



DSX2000 Specifications

		Standard (DSX20-SZH)	Universal (DSX20-UZH)	Motorized (DSX20-MZH)
Zoom Head	Optical system	Telecentric optical system	Telecentric optical system	Telecentric optical system
	Optical zoom ratio	From 1X to 10X	From 1X to 10X	From 1X to 10X
	Optical zoom magnification method	Motorized	Motorized	Motorized
	Calibration	Automatic	Automatic	Automatic
	Nosepiece	Manual sliding nosepiece	Manual sliding nosepiece	Motorized revolving nosepiece
	Number of objectives that can be attached	Up to 2 objectives	Up to 2 objectives	Up to 4 objectives
	Accuracy and repeatability (X-Y plane)	Accuracy* ±3%	±3%	±3%
	Repeatability (Z axis)**	Repeatability 3 on-1	2%	2%
	Repeatability	Repeatability 1 μm	1 μm	1 μm
	Camera	Image sensor	1.1-inch 12.37-megapixel color CMOS image sensor, global shutter	1.1-inch 12.37-megapixel color CMOS image sensor, global shutter
Cooling		Peltier cooling	Peltier cooling	Peltier cooling
Frame rate		60 fps (maximum)	60 fps (maximum)	60 fps (maximum)
Ultra (pixel shift mode)		Not available	6000 × 6000 (1:1), 8192 × 6000 (4:3)	6000 × 6000 (1:1), 8192 × 6000 (4:3)
Super high (3CMOS mode)		Not available	3000 × 3000 (1:1), 4096 × 3000 (4:3)	3000 × 3000 (1:1), 4096 × 3000 (4:3)
Super high		3000 × 3000 (1:1), 4096 × 3000 (4:3)	3000 × 3000 (1:1), 4096 × 3000 (4:3)	3000 × 3000 (1:1), 4096 × 3000 (4:3)
4K mode		3840 × 2160 (16:9)	3840 × 2160 (16:9)	3840 × 2160 (16:9)
High		1500 × 1500 (1:1), 2048 × 1500 (4:3)	1500 × 1500 (1:1), 2048 × 1500 (4:3)	1500 × 1500 (1:1), 2048 × 1500 (4:3)
High (binning 2 × 2)		1500 × 1500 (1:1), 2048 × 1500 (4:3)	1500 × 1500 (1:1), 2048 × 1500 (4:3)	1500 × 1500 (1:1), 2048 × 1500 (4:3)
Full HD mode		1920 × 1080 (16:9)	1920 × 1080 (16:9)	1920 × 1080 (16:9)
Illumination	Color light source	LED	LED	LED
	Lifetime	60,000 h (design value)	60,000 h (design value)	60,000 h (design value)
Observation	BF (brightfield)	Available	Available	Available
	OBQ (oblique)	Available	Available	Available
	DF (darkfield)	Available	Available	Available
	MIX (brightfield + darkfield)	Available	Available	Available
	PO (polarization)	Available	Available	Available
	DIC (differential interference contrast)	Not available	Available	Available
	SR (shaded relief)	Available	Available	Available
	Mechanical aperture for contrast settings	Available	Available	Available
	Mechanical aperture for depth of focus	Not available	Available	Available
	MIX (brightfield + darkfield)	Available	Available	Available
Focus	Focusing	Motorized	Motorized	Motorized
	Stroke	101 mm (motorized)	101 mm (motorized)	75 mm (motorized)

* Calibration by an Evident or a dealer service technician is necessary. To guarantee the accuracy of XY, calibration with a DSX-CALS-HR (calibration sample) is required.
** When used with a 20X or higher objective.

Objective lens		DSX10-SXLOB	DSX10-XLOB	UIS2
Maximum sample height	DSX20-UZH, DSX20-SZH, DSX20-MZH	50 mm	115 mm	145 mm
Maximum sample height (free-angle observation)		50 mm	71 mm	101 mm
Parfocal distance		140 mm	50 mm	50 mm
Total magnification***		140 mm	75 mm	45 mm
Actual FOV		20.9X-1461X	43.8X-5845X	26.1X-7307X
		18182 × 13317 μm	8658 × 6341 μm	14546 × 10654 μm
		260 × 190 μm	65 × 48 μm	52 × 38 μm

*** On a 27-inch 4K monitor, scale setting: 175%, anti-vibration mode: off, fit to window mode.

	DSX20-TMTS	DSX20-RMTS	DSX20-LMTS	U-SIC4R
Stage	XY stage: motorized/manual	Motorized	Motorized	Manual
	XY stroke	100 × 100 mm	Stroke priority mode: 100 mm × 100 mm Rotation priority mode: 50 mm × 50 mm	200 × 100 mm
Transmitted lighting	Integrated (PO, DF, BF, OBQ modes optional)	Not available	Not available	Not available
Rotation angle	Not available	Available Stroke priority mode: ±20° Rotation priority mode: ±90°	Not available	Not available
Display rotation angle	Not available	GUI	Not available	Not available
Maximum load capacity	5 kg (11 lb)	5 kg (11 lb)	5 kg (11 lb)	1 kg (2.2 lb)



	DSX20-UF	DSX20-TF	
Frame	Z-axis stroke	50 mm (manual)	50 mm (manual)
	Tilt observation	Not available	Available: ±90°
	Tilt angle display	Not available	GUI
	Tilt angle method	Not available	Manual, fix/release handle

Macro camera		
Image sensor	1/2.5-inch color CMOS image sensor, rolling shutter	
Image size	1:1 display, 1944 × 1944 4:3 display, 1944 × 1458 Full HD display, 1920 × 1458	
Size of the field of view (horizontal)	81 mm to ∞	

DSX2000 Specifications and Dimensions

		DSX20-UF	DSX20-TF
Display	Screen size	27 inch / 32 inch	
	Resolution	Full HD: 1920 × 1080; 4K: 3840 × 2160	
		Upright frame system	Tilt frame system
System total	Weight (frame, head, motorized stage, display, and console)	54.7 kg (120 lb)	51.7 kg (113 lb)
	Power consumption	100-120V / 220-240 V, 1.1/0.54A, 50 Hz/60 Hz	100-120V / 220-240 V, 1.1/0.54A, 50 Hz/60 Hz
Software			
PRECIV DSX	Included: device control, video recording, time-lapse imaging, large panorama acquisition, extended focus imaging, 3D image acquisition, Z-stack acquisition, position list navigation, best image function, extended 2D measurements, 3D measurements, reporting tools, neural network processing, macro recorder		
Operating system	Windows 11-64 bit		
Network connectivity	Compatible with most popular antiviruses, Windows security updates allowed, images can be saved directly to OneDrive.		
Reporting application	Microsoft 365, Office 2021		
Optional software	Count and Measure, Neural Network Training, Materials Solutions (Grain Size, Cast Iron, Phase Analysis, Porosity, Particle Size Distribution, Non-Metallic Inclusions, Layer Thickness, Coating Thickness).		
Customization	Included: customizable user interface for predefined workflow creation Optional: wafer navigation, automated analysis on specific samples		

Dimensions



DSX20-MZH / DSX20-RMTS / DSX20-TF

